Testing Laboratory of Birla Century, 826, GIDC Industrial Estate, Jhagadia, Bharuch, Gujarat Laboratory

**Accreditation Standard** ISO/IEC 17025: 2005

Page 1 of 2 **Certificate Number** TC-7848 (in lieu of T-2327, T-2328)

Validity 12.09.2018 to 11.09.2020 Last Amended on --

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are performed	Range of Testing / Limits of Detection				
CHEMICAL TESTING								
I.	. TEXTILES (WOVEN & NON WOVENS)							
1.	Finished Fabrics	Dimensional changes of fabrics after Home laundering	AATCC 135: 2015, ISO 6330: 2012, ISO 3759: 2011, ISO 5077: 2007	(+)5.0% to (-)20%				
		pH of the water-extract from wet-processed textiles	AATCC 81: 2016	1 to 14				
		Colour fastness to crocking Colour fastness to	AATCC 8: 2016 (Crockmeter method) AATCC 61 2A: 2013	Qualitative (Grade 1 to 5) Qualitative				
		laundering: Accelerated		(Grade 1 to 5)				

Testing Laboratory of Birla Century, 826, GIDC Industrial Estate, Jhagadia, Bharuch, Gujarat Laboratory

**Accreditation Standard** ISO/IEC 17025: 2005

Page 2 of 2 **Certificate Number** TC-7848 (in lieu of T-2327, T-2328)

Validity 12.09.2018 to 11.09.2020 Last Amended on --

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are performed	Range of Testing / Limits of Detection				
MECHANICAL TESTING								
I.	TEXTILES (WOVEN	& NON WOVENS)						
1.	Finished Fabrics	Warp and Filling count of woven fabrics Width of fabric	ASTM D 3775: 2012 ISO 7211/2: 1984 ASTM D 3774-96: 2016 ISO 22198: 2006	10 per cm to 100 per cms 25 to 250 per inch 100 cms to 300 cms				
		Weight of fabric	ASTM D 3776/3776, M-9a: 2017 ISO 3801:1977	50 GSM to 500 GSM				
		Breaking strength of textile fabrics (Grab test)	ASTM D 5034-09: 2017 ISO 13934-2: 2014	Strength:50 N to 1500 N 5.0 kgf to 150 kgf Elongation:1% to 200%				
		Tearing strength of fabrics by falling-pendulum (Elmendorf-type)	ASTM D 1424-09: 2013 ISO 13937-1: 2000	0.2 N to 57N 200 g to 5700 g				
		Pilling Resistance: Martindale Tester	ASTM D 4970/D4970M-16	Qualitative (Grade 1 to 5)				