Laboratory	Geo Sign Engineering Services, GSES House, Post Office Street, Jamnagar, Gujarat		
Accreditation Standard	ISO/IEC 17025: 2005		
Certificate Number	TC-5449	Page 1 of 3	
Validity	01.04.2018 to 31.03.2020	Last Amended on	

SI.	Product / Material	Specific Test	Test Method Specification	Range of Testing /
	of Test	Performed	against which tests are	Limits of Detection
			performed	

MECHANICAL TESTING

Ι.	BUILDING MATERI	ALS		
1.	Burnt Clay Bricks & Fly Ash Bricks	Compressive strength	IS 3495 (Part 1): 1992 (RA 2016)	2.5 N/mm ² to 20 N/mm ²
		Effloresces	IS 3495 (Part 3): 1992 (RA 2016)	Qualitative
		Water absorption	IS 3495 (Part 2): 1992 (RA 2016)	2 % to 25 %
		Dimension	IS 1077:1992 (RA 2016)	L=4500 mm to 4700 mm
				W=2100 mm to 2300 mm
				H =1300 mm to 1500 mm
2.	Aggregates (Coarse)	Sieve analysis	IS 2386 (Part 1): 1963 (RA 2016)	4.75mm to 80 mm (0.1 % to 100.0 %)
		Flakiness Index	IS 2386 (Part 1): 1963 (RA 2016)	5 % to 40 %
		Elongation Index	IS 2386 (Part 1): 1963 (RA 2016)	5 % to 40 %
		Specific Gravity	IS 2386 (Part 3): 1963 (RA 2016)	1.50 to 3.50
		Water absorption	IS 2386 (Part 3): 1963 (RA 2016)	0.5 % to 5 %
		Crushing Value	IS 2386 (Part 4): 1963 (RA 2016)	5 % to 50 %
3.	Aggregates (Coarse)	Impact Value	IS 2386 (Part 4): 1963 (RA 2016)	5 % to 50 %
		Los Angeles abrasion value	IS 2386 (Part 4): 1963 (RA 2016)	5 % to 50 %
		10% Fine Value	IS 2386 (Part 4): 1963 (RA 2016)	10 kN to 490 kN
4.	Aggregates (Fine)	Sieve analysis	IS 2386 (Part 1): 1963 (RA 2016)	150 μm to 10 mm (0.1 % to 100.0 %)

Laboratory	Geo Sign Engineering Services, GSES House, Post Office Street, Jamnagar, Gujarat		
Accreditation Standard	ISO/IEC 17025: 2005		
Certificate Number	TC-5449	Page 2 of 3	
Validity	01.04.2018 to 31.03.2020	Last Amended on	

SI.	Product / Material Specific Test Test Method S		Test Method Specification	Range of Testing /
	of Test	Performed	against which tests are	Limits of Detection
	1			
		Specific Gravity	IS 2386 (Part 3): 1963	1.50 to 3.50
			(RA 2016)	4.0() 40.0(
		Water absorption	IS 2386 (Part 3): 1963	1 % to 10 %
5	Comont	Consistency	(RA 2010)	25 % to 40 %
5.	(OPC/ PPC)	Consistency	(RA 2014)	25 % 10 40 %
		Initial Setting Time	IS 4031 (Part 5): 1988	30 minutes to 200 minutes
		5	(RA 2014)	
		Final Setting time	IS 4031 (Part 5): 1988	100 minutes to
			(RA 2014)	600 minutes
		Compressive strength	IS 4031 (Part 6): 1988	10 N/mm ² to 70 N/mm ²
			(RA 2014)	
		Soundness with Le-	IS 4031 (Part-3):1988	0.05 mm to 10 mm
		Chattalier method	(RA 2014)	<u> </u>
		Fineness by blaine air	IS 4031 (Part 2): 1999	100 m²/kg to 400 m²/kg
		permeability	(RA 2013)	
6.	Concrete	Compressive strength	IS 516:1959 (RA 2013)	10 N/mm ² to 70 N/mm ²
<u></u>		Flexural strength	IS 516:1959 (RA 2013)	2.0 N/mm ² to 8.0 N/mm ²
7.	Paver Block	Water absorption	IS 15658 (Annex-C) 2006 (RA 2011)	1% to 15%
		Compressive Strength	IS 15658 (Annex-D) 2006 (RA 2011)	5 N/mm ² to 60 N/mm ²
II.	SOIL & ROCK			
1.	Soil	Grain size analysis	IS 2720 (Part 4): 1985 (RA 2015)	100 m ² /kg to 400 m ² /kg
		Liquid Limit	IS 2720 (Part 5): 1985	75 μ m to 40 mm
		Plantia Limit	18 2720 (Dort 5): 1095	(0.1% 10100.0%)
		FIASUU LIITIIL	(RA 2015)	20 % 10 120 %
		Shrinkage Limit	IS 2720 (Part 6): 1985 (RA 2011)	15 % to 40 %

Lab	oratory	Geo Sign Engineering Services, GSES House, Post Office Street, Jamnagar, Gujarat			
Acc	reditation Standard	ISO/IEC 17025: 2005			
Cer	tificate Number	TC-5449		Page 3 of 3	3
Vali	dity	01.04.2018 to 31	.03.2020	Last Amen	ded on
SI.	Product / Material	Specific Test	Test Meth	nod Specification	Range of Testing /

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are performed	Range of Testing / Limits of Detection
		Light compaction	IS 2720 (Part 7): 1985 (RA 2011)	MDD-1.0 g/cc to 2.10 g/cc
		Heavy compaction	IS 2720 (Part 8): 1985 (RA 2015)	MDD-1.4 g/cc to 2.60 g/cc OMC-2 % to 30.0 %
		California Bearing ratio	IS 2720 (Part 16): 1985 (RA 2011)	1 % to 60 %