

Laboratory Geo Engineering Services, 1542, Pashupatinath Nagar, Godi Road,
Dahod, Gujarat

Accreditation Standard ISO/IEC 17025: 2005

Certificate Number TC-7474 (in lieu of T-2966 & T-4003)

Page 1 of 5

Validity 24.05.2018 to 23.05.2020

Last Amended on 22.06.2018

| Sl. | Product / Material of Test | Specific Test Performed | Test Method Specification against which tests are performed | Range of Testing / Limits of Detection |
|-----|----------------------------|-------------------------|---|--|
|-----|----------------------------|-------------------------|---|--|

CHEMICAL TESTING

| I. | WATER | | | |
|----|--|-----------------------------|--------------------------------------|-----------------------|
| 1. | Water (Construction Water, Domestic Water, Irrigation Water, Bore Water, Distilled Water, Waste Water) | pH @ 25°C | IS 3025 (Part 11):1983, (RA 2017) | 1 to 13 |
| | | Sulphate as SO ₄ | IS 3025 (Part 24):1986 (RA 2014) | 1 mg/l to 2000 mg/l |
| | | Chloride as Cl | IS 3025 (Part 32):1988 (RA 2014) | 0.5 mg/l to 3000 mg/l |

Venugopal C
Convenor

N. Venkateswaran
Program Manager

Laboratory **Geo Engineering Services, 1542, Pashupatinath Nagar, Godi Road, Dahod, Gujarat**

Accreditation Standard **ISO/IEC 17025: 2005**

Certificate Number **TC-7474 (in lieu of T-2966 & T-4003)**

Page 2 of 5

Validity **24.05.2018 to 23.05.2020**

Last Amended on **22.06.2018**

| Sl. | Product / Material of Test | Specific Test Performed | Test Method Specification against which tests are performed | Range of Testing / Limits of Detection |
|-----|----------------------------|-------------------------|---|--|
|-----|----------------------------|-------------------------|---|--|

MECHANICAL TESTING

| I. MECHANICAL PROPERTIES OF METALS | | | | |
|---|--|---------------------------------------|---|--|
| 1. | Reinforcing Steel (Up to 20mm Diameter) | Yield Strength | IS 1608:2005, (RA 2017) | 4 kN to 600 kN(Load) |
| | | Ultimate Strength | IS 1608:2005, (RA 2017) | 4 kN to 600 kN(Load) |
| | | Elongation, % | IS 1608:2005, (RA 2017) | 5 % to 30 % |
| | | Nominal Weight of Steel | IS 1608:2005, (RA 2017) | 0.1 Kg/m to 10 Kg/m |
| | | Bend | IS 1599-2012, (RA 2017) | 8 mm to 20 mm |
| | | Rebend | IS 1786-2008, (RA 2013) | 8 mm to 20 mm |
| II. BUILDING MATERIAL | | | | |
| 1. | Coarse Aggregates | Sieve Analysis, % | IS 2386 (Part 1):1963 (RA 2016), Amndt 04 | (0 to 100%) Sieve Size- 4.75 mm to 90 mm |
| | | Abrasion value (Loss Angeles Machine) | IS 2386 (Part 4):1963 (RA 2016), Amndt 03 | 2 % to 50 % |
| | | Impact value | IS 2386 (Part 4):1963 (RA 2016), Amndt 03 | 2 % to 50 % |
| | | Crushing value | IS 2386 (Part 4):1963 (RA 2016), Amndt 03 | 2 % to 50 % |
| | | Specific Gravity | IS 2386 (Part 3):1963 (RA 2016) | 1.5 to 3.5 |
| | | Water absorption | IS 2386 (Part 3):1963 (RA 2016) | 0.1 % to 10 % |
| | | Flakiness Index | IS 2386 (Part 1):1963 (RA 2016), Amndt 04 | 1 % to 45 % |
| | | Elongation Index | IS 2386 (Part 1):1963 (RA 2016), Amndt 04 | 1 % to 45 % |
| | | Bulk Density | IS 2386 (Part 3):1963 (RA 2016) | 1 kg/l to 2.5 kg/l |

Laboratory

Geo Engineering Services, 1542, Pashupatinath Nagar, Godi Road,
Dahod, Gujarat

Accreditation Standard ISO/IEC 17025: 2005

Certificate Number TC-7474 (in lieu of T-2966 & T-4003)

Page 3 of 5

Validity 24.05.2018 to 23.05.2020

Last Amended on 22.06.2018

| Sl. | Product / Material of Test | Specific Test Performed | Test Method Specification against which tests are performed | Range of Testing / Limits of Detection |
|-----|-----------------------------------|------------------------------------|---|---|
| | | Soundness | IS 2386 (Part 5):1963 (RA 2016) | 1 % to 30 % |
| 2. | Fine Aggregates | Sieve Analysis, % | IS 2386 (Part 1):1963 (RA 2016), Amndt 04 | (0 to 100%) Sieve Size- 0.075 mm to 4.75 mm |
| | | Specific Gravity | IS 2386 (Part 3):1963 (RA 2016) | 1.5 to 3.5 |
| | | Water absorption | IS 2386 (Part 3):1963 (RA 2016) | 0.5 % to 10 % |
| | | Bulk Density | IS 2386 (Part 3):1963 (RA 2016) | 1 kg/l to 2.5 kg/l |
| | | Soundness | IS 2386 (Part 5):1963 (RA 2016) | 1 % to 20 % |
| 3. | Burnt Clay Building Bricks | Compressive Strength | IS 3495 (Part 1):1992 (RA 2016) | 1.5 N/mm ² to 15 N/mm ² |
| | | Water absorption | IS 3495 (Part 2):1992 (RA 2016) | 5 % to 30 % |
| | | Dimension Test | IS 1077:1992 (RA 2016) Amndt 01 | 500 mm to 5000 mm |
| | | Efflorescence | IS 3495(Part 3):1992 (RA 2016) | Qualitative |
| 4. | Hardened Concrete | Compressive Strength | IS 516:1959 (RA 2013), Amndt 2 | 5 N/mm ² to 80 N/mm ² |
| 5. | Cement (OPC, PPC, PSC) | Fineness by Blain Air Permeability | IS 4031 (Part 2):1999 (RA 2013), Amndt 01 | 200 m ² /kg to 400 m ² /kg |
| | | Consistency | IS 4031 (Part 4):1988 (RA 2014), Amndt 01 | 20 % to 40 % |
| | | Initial Setting Time | IS 4031 (Part 5):1988 (RA 2014), Amndt 02 | 5 min to 300 min |
| | | Final Setting Time | IS 4031 (Part 5):1988 (RA 2014), Amndt 02 | 30 min to 700 min |
| | | Soundness (By Le Chatelier Method) | IS 4031 (Part 3):1988 (RA 2014), Amndt 02 | 0.5 mm to 10 mm |
| | | Compressive Strength | IS 4031 (Part 6):1988 (RA 2014), Amndt 04 | 10 N/mm ² to 70 N/mm ² |

Laboratory **Geo Engineering Services, 1542, Pashupatinath Nagar, Godi Road, Dahod, Gujarat**

Accreditation Standard **ISO/IEC 17025: 2005**

Certificate Number **TC-7474 (in lieu of T-2966 & T-4003)**

Page 4 of 5

Validity **24.05.2018 to 23.05.2020**

Last Amended on 22.06.2018

| Sl. | Product / Material of Test | Specific Test Performed | Test Method Specification against which tests are performed | Range of Testing / Limits of Detection |
|------------|----------------------------|---------------------------|---|---|
| | | Density | IS 4031 (Part 11):1988 (RA 2014) | 2.5 g/cc to 3.5 g/cc |
| 6. | Paver Block | Compressive Strength | IS 15658:2006 (RA 2017), Annex-D | 5 N/mm ² to 60 N/mm ² |
| | | Water absorption | IS 15658:2006 (RA 2017), Annex-C | 1.0 % to 15 % |
| 7. | Bitumen | Specific Gravity | IS 1202:1978 (RA 2013) | 0.5 to 1.5 |
| | | Penetration Test | IS 1203:1978 (RA 2013) | 1 to 400(1/10mm) |
| | | Softening Point Test | IS 1205:1978 (RA 2014) | 10°C to 100 °C |
| | | Ductility Test | IS 1208:1978 (RA 2014) | 1 cm to 100 cm |
| | | Flash Point | IS 1209:1978 (RA 2014) | 70°C to 500 °C |
| | | Absolute Viscosity | IS 1206(Part 2):1978 (RA 2014) | 100 poises to 8000 poises |
| | | Kinematic Viscosity | IS 1206(Part 3):1978 (RA 2014) | 60 cSt to 1000 cSt |
| | | Marshall Stability | ASTM D-6927-15 | 1 kN to 25 kN |
| | | Marshall Flow Value | ASTM D-6927-15 | 0.5 mm to 30 mm |
| | | Binder content | IRC SP-11-1984 Appendix-5(C) | 0.5 % to 10 % |
| 8. | Fresh Concrete | Slump Test | IS 1199:1959 (RA 2013) | 10 mm to 200 mm |
| II. | SOIL AND ROCK | | | |
| 1. | Soil | Atterberg's Limit | IS 2720(Part 5):1985 (RA 2015) | 10 % to 100 % |
| | | Liquid Limit | IS 2720(Part 5):1985 (RA 2015) | 10 % to 100 % |
| | | Plastic Limit | IS 2720(Part 5):1985 (RA 2015) | 10 % to 100 % |
| | | Light Compaction Test MDD | IS 2720 (Part 7):1980 (RA 2016), Amndt 2 | 1.5 g/cc to 2.5 g/cc |
| | | OMC | | 1 % to 30 % |
| | | Heavy Compaction Test MDD | IS 2720 (Part 8):1983 (RA 2015) | 1.5 g/cc to 2.5 g/cc |
| | | OMC | | 1 % to 30 % |

Laboratory **Geo Engineering Services, 1542, Pashupatinath Nagar, Godi Road, Dahod, Gujarat**

Accreditation Standard **ISO/IEC 17025: 2005**

Certificate Number **TC-7474 (in lieu of T-2966 & T-4003)**

Page 5 of 5

Validity **24.05.2018 to 23.05.2020**

Last Amended on 22.06.2018

| Sl. | Product / Material of Test | Specific Test Performed | Test Method Specification against which tests are performed | Range of Testing / Limits of Detection |
|-----------|----------------------------|---|---|---|
| | | Specific Gravity | IS 2720(Part 3) (Sec:1):1980 (RA 2016) | 1.1 to 3.0 |
| | | Free Swell Index | IS 2720 (Part 40):1977 (RA 2016) | Upto 500 % |
| | | Grain Size Analysis | IS 2720 (Part 4):1985 (RA 2015) | (0 to 100 %) 75micron to 10 mm |
| | | Direct Shear Test (Undrained) Cohesion | IS 2720 (Part 13):1986 (RA 2016) Amndt 01 | Upto 1kg/cm ² |
| | | Angle of internal friction | | Upto 45 degree |
| | | Laboratory Permeability Test Constant Head Permeability | IS 2720 (Part 17):1986 (RA 2016) | 10 ⁻¹ cm/s to 10 ⁻⁵ cm/s |
| | | Falling Head Permeability | | 10 ⁻⁴ cm/s to 10 ⁻⁷ cm/s |
| | | CBR-Soaked | IS 2720 (Part 16):1987 (RA 2016) | 0.5 % to 50 % |
| | | CBR-Un soaked | | 0.5 % to 50 % |
| | | Unconfined Compressive Strength | IS 2720 (Part 10):1991 (RA 2015) | 0.25 kg/cm ² to 3 kg/cm ² |
| 2. | Soil (Field Test) | Field Density test Core Cutter Method | IS 2720 (Part 29):1975 (RA 2015) | 1.5 g/cc to 2.5 g/cc |
| | | Field Moisture test by Core Cutter Method | IS 2720 (Part 29):1974 (RA 2015) | 1 % to 20 % |
| | | Field Density test Sand Replacement Method | IS 2720 (Part 28):1974 (RA 2015) Amndt 01 | 1.5 g/cc to 2.5 g/cc |
| | | Field Moisture test by Sand Replacement Method | IS 2720 (Part 28):1974 (RA 2015) | 1 % to 20 % |
| 3. | Rock | Unconfined Compressive Strength | IS 9143:1979, (RA 2016) | 10 N/mm ² to 90 N/mm ² |
| | | Water Content | IS 13030:1991, (RA 2016) | 0.5 % to 10 % |
| | | Porosity | IS 13030:1991, (RA 2016) | 1 % to 50 % |
| | | Density | IS 13030:1991, (RA 2016) | 1 g/cc to 4 g/cc |