Laboratory Testing Laboratory of Steelcast Limited, Ruvapari Road, Bhavnagar,

Gujarat

Accreditation Standard ISO/IEC 17025: 2005

Certificate Number TC-6863 Page 1 of 2

Validity 07.02.2018 to 06.02.2020 Last Amended on --

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are	Range of Testing / Limits of Detection
			performed	

CHEMICAL TESTING

I.	METALS & ALLOYS			
1.	Carbon Steel and	Carbon	ASTM E 415: 2017	0.032% to 1.2%
	Low Alloy Steel	Silicon	IS 8811:1998	0.10% to 1.71%
		Manganese	(RA 2012)	0.16% to 1.546%
		Phosphorus	JIS 1253: 2002	0.005% to 0.0611%
		Sulfur	(RA 2013)	0.005% to 0.070%
		Chromium		0.064% to 3.00%
		Nickel		0.050% to 1.60%
		Molybdenum		0.010% to 1.30%
		Vanadium		0.010% to 0.30%
		Copper		0.010% to 0.50%
		Tin		0.003% to 0.060%
		Aluminum		0.012% to 0.100%
		Titanium		0.010% to 0.100%
		Nitrogen		0.0020% to 0.0150%
2.	High chromium	Carbon	IS 15338: 2003	0.080% to 3.000%
	Cast Iron, High	Silicon	(RA 2013)	0.50% to 1.10%
	Alloy Steel and	Manganese	ASTM E 1086: 2014	0.60% to 1.70%
	Stainless Steel	Phosphorus	IS 9879:1998	0.010% to 0.050%
		Sulfur	(RA 2015)	0.020% to 0.040%
		Chromium	JIS 1253: 2002	17.00% to 25.00%
		Nickel	(RA 2013)	1.00% to 15.00%
		Molybdenum		0.10% to 3.00%
		Vanadium		0.01% to 1.00%
		Copper		0.050% to 0.50%
3.	High Manganese	Carbon	ASTM E 2209: 2013	1.00% to 1.20%
	Steel	Silicon	JIS 1253: 2002	0.30% to 1.10%
		Manganese	(RA 2013)	9.00% to 17.00%
		Phosphorus		0.040% to 0.050%
		Sulfur		0.004% to 0.010%
		Chromium		1.00% to 1.50%
		Molybdenum		0.60% to 1.30%

K. Siri Babu Convenor Laboratory Testing Laboratory of Steelcast Limited, Ruvapari Road, Bhavnagar,

Gujarat

Accreditation Standard ISO/IEC 17025: 2005

Certificate Number TC-6863 Page 2 of 2

Validity 07.02.2018 to 06.02.2020 Last Amended on --

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are	Range of Testing / Limits of Detection
			performed	

MECHANICAL TESTING

I.	MECHANICAL PROP	PERTIES OF METALS		
1.	Ferrous materials,		ISO 6892 1: 2016	200 MPa to 1050 MPa
		L	ASTM A370: 2017	200 MPa to 1050 MPa
		Ultimate Tensile Strength		350 MPa to 1250 MPa
		Elongation		1% to 60%
		Reduction in Area		1% to 70%
		Charpy "V" Notch	ISO 148 1: 2016	2 J to 300 J
		((-)40°C to 27°C)		
		Izod "V" Notch	IS 1598:1977	2 J to 168 J
		(Room Temperature)	(RA 2015)	
ļ		Brinell Hardness	ISO 6506 1:2014	90 HBW to 560 HBW
			ASTM E10: 2017	(3000kgf/10mm)
		Bend Test	IS 1599: 2012	Qualitative
			(RA 2017)	(Mandrel Diameter 10, 20,
			·	24, 30, 36, 40, 48, 50, 60,
				84, 100 mm)

K. Siri Babu Convenor