Accreditation Standard ISO/IEC 17025: 2005

Page 1 of 6 **Certificate Number** TC-7120

Validity 13.04.2018 to 12.04.2020 Last Amended on --

SI.	Product / Material	Specific Test	Test Method Specification	Range of Testing /
	of Test	Performed	against which tests are	Limits of Detection
			performed	

CHEMICAL TESTING

I.	METALS AND ALL	.OYS		
1.	Low Alloy Steel	Carbon	IS 8811: 1998 (RA 2012)	0.08% to 0.7%
		Manganese		0.19% to 0.56%
		Silicon		0.6% to 1.18%
		Sulphur		0.01% to 0.04%
		Phosphorous		0.014% to 0.074%
		Chromium		0.77% to 3.0%
		Nickel		0.39% to 3.0%
		Molybdenum		0.3% to 0.8%
		Copper		0.2% to 0.44%
		Vanadium		0.008% to 0.44%
2.	Stainless steel	Carbon	IS 9879: 1998 (RA 2015)	0.056% to 0.07%
		Manganese		0.4% to 1.39%
		Silicon		0.39% to 0.51%
		Sulphur		0.01% to 0.03%
		Phosphorous		0.01% to 0.026%
		Chromium Nickel	4.2% to 24.92%	
				0.32% to 19.55%
		Molybdenum		0.23% to 2.5%
		Copper		0.1% to 1.8%
		Vanadium		0.04% to 0.092%
3.	Aluminium & Its	Silicon	ASTM E 1251-17	0.5% to 8.9%
	Alloys	Iron		0.6% to 0.8%
		Manganese		0.01% to 0.04%
		Magnesium		0.04% to 2.89%
		Zinc		0.04% to 0.37%
		Copper		0.05% to 1.87%
4.	Copper &	Lead	BS EN 15079:2015	0.0052% to 5.13%
	Its alloys	Tin		0.0002% to 5.22%
		Iron		0.0005% to 0.14%

Accreditation Standard ISO/IEC 17025: 2005

Page 2 of 6 **Certificate Number** TC-7120

Validity 13.04.2018 to 12.04.2020 Last Amended on --

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are performed	Range of Testing / Limits of Detection
		Nickel		0.0002% to 1.0%
		Zinc		0.003% to 38.8%
II.	PAINTS & SURFAC	E COATING		
1.	Paints & Enamels	Drying Time	IS 101 (Part 3/Sec 1): 1986 (RA 2012)	Up to 12 h
		Consistency	IS 101 (Part 1/Sec 5): 1989 (RA 2009)	60 s to 120 s
		Mass	IS 101 (Part 1/Sec 7): 1987 (RA 2009)	8.5 kg/10L to 18 kg/10L
		Volume Solids	IS 101 (Part 8/Sec 6): 1993 (RA 2009)	30% to 80%
		Wet Opacity	IS 101 (Part 4/Sec 1): 1988 (RA 2009)	100 m ² /10L to 500 m ² /10L
		Scratch Hardness	IS 101 (Part 5/Sec 2): 1988 (RA 2009)	Qualitative
		Gloss value at 60°	IS 101 (Part 4/Sec 4): 1988 (RA 2012)	5 Gloss to 120 Gloss
		Fineness of grind	IS 101 (Part 3/Sec 5): 1987 (RA 2009)	5 Micron to 100 Micron
		Flash point	IS 101 (Part 1/Sec 6): 1987 (RA 2009)	20°C to 50°C
		Flexibility & Adhesion	IS 101 (Part 5/Sec 2): 1988 (RA 2009)	Qualitative
		Accelerated Storage stability test	IS 8662: 2004 (RA 2009)	Qualitative
		Pigment content	IS 101(Part 8/Sec 2): 1990 (RA 2012)	1% to 60%
		Resistance to 5% H ₂ SO ₄	ICFMDSpec 045, Annexure A	Qualitative
		Resistance to 5% Na ₂ CO ₃	ICFMDSpec 045, Annexure B	Qualitative

ISO/IEC 17025: 2005 **Accreditation Standard**

Page 3 of 6 **Certificate Number** TC-7120

Validity 13.04.2018 to 12.04.2020 Last Amended on --

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are performed	Range of Testing / Limits of Detection
		Volatile matter	IS 101(Part 2/Sec 2): 1986 (RA 2012)	10% to 99%
		Dry Film Thickness	IS 101 (Part 3/Sec 2): 1989 (RA 2009)	10 Microns to 200 Microns

Accreditation Standard ISO/IEC 17025: 2005

Page 4 of 6 **Certificate Number** TC-7120

Validity 13.04.2018 to 12.04.2020 Last Amended on --

•	Product / Material	Specific Test	Test Method Specification	
-	of Test	Performed	against which tests are	Limits of Detection
			performed	

ELECTRICAL TESTING

I.	INSULATING MATE			
	LIQUID			
	DIELECTRIC	Acetylene	IS 10593: 2006 (RA 2011) IS 9434: 1992 (RA 2013)	1 ppm to 150 ppm
	MATERIALS- Transformer Oil (Mineral Insulating	Carbon dioxide		1 ppm to 12000 ppm
		Hydrogen		1 ppm to 300 ppm
		Ethane		1 ppm to 1000 ppm
	Oil)	Ethylene		1 ppm to 400 ppm
		Methane		1 ppm to 300 ppm

Accreditation Standard ISO/IEC 17025: 2005

Page 5 of 6 **Certificate Number** TC-7120

Validity 13.04.2018 to 12.04.2020 Last Amended on --

į.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are	Range of Testing / Limits of Detection	_
			performed		i

MECHANICAL TESTING

I.	MECHANICAL PRO				
1.	Ferrous, Aluminium, Copper metals,	Tensile Strength % Elongation		IS 1608: 2005 (RA 2017)	100 MPa to 750 MPa (20 kN to 1000 kN)Load 5% to 60%
	alloys & products	Brinell Hardness	HBW 10/3000 HBW 5/750	IS 1500 (Part 1): 2013	140 HBW to 500 HBW 10/3000 100 HBW to 500 HBW 5/750
		Rockwell Ha (HRBW)		IS 1586 (Part 1): 2012 (RA 2017)	55 HRBW to 100 HRBW
		Rockwell Hardness (HRC)			20 HRC to 70 HRC
		ļ	dness (HV5) dness (HV30)	IS 1501 (Part 1): 2013	120 HV5 to 900 HV5 200 HV30 to 1000 HV30
II.	METALLOGRAPHY	TEST			
1.	Steel and cast iron Materials and Products	Microstructure		ASTM handbook Atlas of Microstructure Vol No. VII, 8 th Edition IS 7739 (Part 1)-1975 (RA 2010)	Qualitative 50X, 100X,250X and 500X
2.	Cast Iron material and products	Microstructu	re of graphite	IS 7754: 1975 (RA 2012)	Qualitative 100X

Accreditation Standard ISO/IEC 17025: 2005

Page 6 of 6 **Certificate Number** TC-7120

Validity 13.04.2018 to 12.04.2020 Last Amended on --

SI.	Product / Material of Test	Specific Test Performed	Test Method Specification against which tests are	Range of Testing / Limits of Detection	
			performed		

NON DESTRUCTIVE TESTING

I.	METALS AND ALLOYS			
1.	Various types of axles & Discs (Forged Components)	Ultrasonic Testing - Detection of internal Flaws	RDSO/M&C Test method:- 1) k-405/ Revised on May 2017 2) MC-34/Revised on May 2017 3)MC-111/Revised on Oct 2006 4) MC-95/Revised on Mar 2006 5) MC-11/Revised on Sep 1991 6) MC-13/Revised on May 1999 7) MC-162/ Revised on Mar 2014 8) MC-7/Revised on Sep	7mm to 2500mm
			2007	
	Dallas Dani's sant	Description of Teachers	9) IRS-R-34/2003	7mm to 200mm
2.	Roller Bearing of coaches	Penetrant Testing - Fluorescent Water Washable	CMT/NDT/TP/PT/01 Issue No. 1 Date 06.02.2018	Qualitative