

<b>Laboratory</b>	<b>QC Laboratory, Tiki Tar Industries (Baroda) Limited, Village Road, Bhandup (West), Mumbai, Maharashtra</b>		
<b>Accreditation Standard</b>	<b>ISO/IEC 17025: 2005</b>		
<b>Discipline</b>	<b>Chemical Testing</b>	<b>Issue Date</b>	<b>03.02.2015</b>
<b>Certificate Number</b>	<b>T-1497</b>	<b>Valid Until</b>	<b>02.02.2017</b>
<b>Last Amended on</b>	<b>-</b>	<b>Page</b>	<b>1 of 1</b>

<b>S.No.</b>	<b>Product / Material of Test</b>	<b>Specific Test Performed</b>	<b>Test Method Specification against which tests are performed</b>	<b>Range of Testing / Limits of Detection</b>
<b>I.</b>	<b>PETROLEUM</b>			
<b>1.</b>	<b>Bituminous asphalt, tars and allied products</b>			
<b>a.</b>	<b>Paving Bitumen Industrial Bitumen Modified Bitumen (CRMB/PMB/NRMB)</b>	Loss on heating	IS 1212: 1978 (RA 2009)	(0.01 to 2.0) %
<b>b.</b>	<b>Anti-stripping agent</b>	Pour Point	IS 1448 (Part 10 ): 1970 (RA 2008)	(15 to 27 ) °C
	<b>Sealing Compound (Grade A &amp; B)</b>	Pour Point	IS 1834: 1984 (RA 2005)	(25 to 180) °C
<b>c.</b>	<b>Industrial Bitumen Paving Bitumen RBA Compound</b>	Solubility in trichloroethylene	IS 1216: 1978	(50 to 100) %
<b>d.</b>	<b>Industrial Bitumen Paving Bitumen Modified Bitumen (CRMB/PMB/NRMB)</b>	Flash Point	IS 1448 (Part 69): 1969	(80 to 350) °C

**-X-X-X-X-X-X-X-X-X-X-X-X-**

**Anuja Anand  
Convenor**

**N. Venkateswaran  
Program Manager**