

<b>Laboratory</b>	<b>QC Laboratory, Tiki Tar Industries (Baroda) Limited, Village Road, Bhandup (West), Mumbai, Maharashtra</b>		
<b>Accreditation Standard</b>	<b>ISO/IEC 17025: 2005</b>		
<b>Discipline</b>	<b>Mechanical Testing</b>	<b>Issue Date</b>	<b>03.02.2015</b>
<b>Certificate Number</b>	<b>T-1498</b>	<b>Valid Until</b>	<b>02.02.2017</b>
<b>Last Amended on</b>	<b>-</b>	<b>Page</b>	<b>1 of 1</b>

<b>S.No.</b>	<b>Product / Material of Test</b>	<b>Specific Test Performed</b>	<b>Test Method Specification against which tests are performed</b>	<b>Range of Testing / Limits of Detection</b>
<b>I. BUILDINGS MATERIALS</b>				
<b>1. Bitumen</b>				
<b>a.</b>	<b>Paving Bitumen Industrial Bitumen Modified Bitumen (CRMB / PMB etc) Sealing Compound (Grade A &amp; B) Emulsified Bitumen (Cationic type)</b>	Penetration at 25 °C, 100 g	IS 1203: 1978 (RA 2008)	(5 to 200) mm
<b>b.</b>	<b>Industrial Bitumen Paving Bitumen Modified Bitumen RBA Compound</b>	Softening Point	IS 1205: 1978 (RA 2009)	(35 to 140) °C
<b>c.</b>	<b>Paving Bitumen Industrial Bitumen Modified Bitumen (CRMB / PMB etc) Emulsified Bitumen</b>	Ductility at 25°C	IS 1208: 1978 (RA 2009)	(1 to 100) cm

**-X-X-X-X-X-X-X-X-X-X-X-X-**

**Anuja Anand  
Convenor**

**N. Venkateswaran  
Program Manager**